

VINSAK TTR



VINSAK Table Top Rewinder

The VINSAK TTR has been specifically developed to offer a robust table top rewinder with many features normally only found on larger more expensive inspection/slitting equipment. Accurate tension controls settings can be achieved with independent air operated unwind and rewind tension controls.

Equipped with pneumatically inflating mandrels that ensure positive grip without distorting label core and finished reel. The table top can be tilted towards the operator for increased flexibility and easy operation.

FEATURES

- ✓ Splicing table.
- ✓ Label in/label out rewind capability.
- ✓ Easy programmable label/length counter
- ✓ Adjustable table tilt for easy operation
- ✓ Bidirectional

SPECIFICATION

Maximum width of band 250mm
Maximum rewind diameter 300mm

Unwind and winding

Winding units 2pcs.
Max diameter of rewind 2x440mm
Pneumatic clamp diameter 25-76mm
Max. rewind velocity 78-150m/min

Electronic counter (label unit & meters)

Voltage supply 220-240V/10 Amp
Power frequency 50Hz (60Hz optional)

OPTIONS

- ✓ Inkjet printing facility.
- ✓ Missing label detecting system.
- ✓ Maximum 2 Razor Blade for one station & Minimum width cut 20mm
- ✓ Stroboscope attachment

Wattage rating 2.0 KW
Average air demand 0,81/min
Working pressure 3 bar
Dimensions (LxWxH) 860x1110x1050
Approximate Weight 200kg

Operating conditions

Max. temp +40°C (104°F)
Min temp +5°C (41°F)
Relative humidity 10-40%

